



Surface Mount



Magnet Mount

High Gain, DSRC with GPS Surface or Magnet Mount

- Ideal for ITS/Smart Highway Trials
- Available in either Surface-mount or Mag-mount
- High Gain Performance on DSRC, 6 dBi

Mobile Mark's high gain DSRC antennas are specifically designed for ITS (Intelligent Transportation Systems), and used for Smart Highway trials and Vehicle-to-Vehicle (V2V) in ITS trials.

Standard connectors are SMA Plug (Male) on both cables. The antenna radomes are available in black, and the case material is made out of polycarbonate.

These antennas operate on the DSRC (Dedicated Short Range Communications) band, with the frequency covering 5850-5930 MHz.

The antennas can handle a maximum power of 10 Watts. The elevation beamwidth is 30 degrees, and the azimuth beamwidth is 360 degrees.

The SM6-5900/1575 antenna can be mounted to a vehicle's metal surface or any bulkhead through a 3/4" hole (19mm). The MAG6-5900/1575 is mounted with a magnet mount. These antennas are provided with two cables, low loss-195 for DSRC and RG-174 for GPS.

Model #	Mounting
SM6-5900/1575-3C2C-BLK-180	Surface Mount
MAG6-5900/1575-3C2C-BLK-120	Magnet Mount
Optional combination GPS/Glonass available	
Available in Black Only	

The SM6-5900/1575 antenna measures 5.3" (135mm) from the tip of the Radome Cap to the bottom of the antenna base, while the MAG6-5900/1575 measures 5.5" (140mm).

Specifications			
Frequency:		MAG6 Cable Length:	10 Feet (4m)
DSRC:	5850-5930 MHz	Case Material:	Polycarbonate
GPS:	1575 MHz	SM6 Dimensions:	5.3" (135 mm) tall, base is 2 5/8" D (67 mm)
GLONASS (Optional):	1602 MHz	SM6 Mounting (Stud):	3/4" dia x 1/2" long thread (19 mm x 12 mm) for 3/16" thick (4.8 mm)
DSRC Gain:	6 dBi	MAG6 Dimensions:	5.5 (140mm) tall, base is 2 5/8" D (67mm)
VSWR:	2:1 max over range	MAG6 Mounting:	Metal Surface
Nominal Impedance:	50 ohms	Connector:	SMA/SMA Plug (Male) standard
Maximum Power:	10 Watts	Shock & Vibration:	EN 61373, TIA-329.2-C
GPS Gain:	1575 +/- 2 MHz, LNA 26 dB 5 dBi nominal RHCP	Water Ingress:	IPx5
Amplifier Bias:	3.3 to 5 VDC		
Current:	20 mA max, 10 mA typical		
Elevation Beamwidth:	30 degrees (peak at horizon)		
Azimuth Beamwidth:	360 degrees		
Cable:			
GPS	RG-174		
DSRC	low loss-195		
SM6 Cable Length:	15 Feet (4.5m)		