

Technical Specification

430-490 MHz 3dBd GAIN

A1143A, B A2143A, B CLASSIC MOBILE ANTENNAS

High Performance: 3dBd gain is achieved in this premium antenna featuring a 5/8 over 1/4 wave design.

Stylish and Durable: These antennas are manufactured using the finest corrosion resistant materials and finishes available. The enclosed silver plated phasing coil insures dependable operation

Reliable: The ABS base has an ultrasonically welded brass insert and a spring loaded contact for long term reliability.

Standard Mounting: These antennas mate with a standard TAD/NMO type mount, providing an excellent moisture seal even when the antenna is removed.

A2143A, B

An integrated magnet mount version of this antenna is also available. It features a powerful magnetic base with a protective mylar to prevent damage to any mounting service. It is supplied with 12 feet of RG58U coax and choice of either PL259 or TYPE N connector.

ELECTRICAL SPECIFICATIONS:

FREQUENCY RANGE: 430-490MHz

GAIN: 3dBd
VSWR: <2:1
IMPEDANCE: 50 ohms
POWER RATING: 200 watts
RADIATOR: Stainless steel

MATCHING COILS: Silver plated, enclosed coils ABS, Ultrasonic brass insert

CONTACT: Spring loaded contact

LENGTH: 26" (66cm)

MOUNTING: Standard TAD/NMO type

FINISH: Brite or Black

A1185 Permanent Mount
FREQUENCY BRITE BLACK
BRITE BLACK
BRITE BLACK
A30-490MHz A1143A A1143B A2143A A2143B



Vertical Pattern

