

High Performance: 3dB gain is achieved in this premium antenna featuring a 5/8 wave over 1/4 wave design.

Stylish and Durable: These antennas are manufactured using the finest corrosion resistant materials and finishes available. The enclosed silver plated phasing coil insures dependable operation

Reliable: The ABS base has an ultrasonically welded brass insert and a gold plated spring loaded contact for long term reliability.

Standard Mounting: These antennas mate with a standard TAD/NMO type mount, providing an excellent moisture seal even when the antenna is removed.



ELECTRICAL SPECIFICATIONS:

| | |
|-------------------------|------------|
| FREQUENCY RANGE: | 746-869MHz |
| GAIN: | 3dBd |
| VSWR: | <2:1 |
| IMPEDANCE: | 50 ohms |
| POWER RATING: | 200 watts |

MECHANICAL SPECIFICATIONS:

| | |
|-----------------------|-----------------------------------|
| RADIATOR: | Stainless steel |
| MATCHING COIL: | Silver plated, enclosed coil |
| BASE: | ABS, Ultrasonic brass insert |
| CONTACT: | Gold plated spring loaded contact |
| LENGTH: | 15" (38 cm) at lowest frequency |
| SHOCK SPRING: | Stainless steel |
| MOUNTING: | Standard TAD/NMO type |
| FINISH: | Brite or Black |