

Technical Specification

2400-2500MHz, 3dBi Gain

BASE STATION ANTENNA

Reliable Performance: Rated at 100 watts, you can expect years of continuous service.

Construction: The radiating elements are collinear stacked and phased copper alloy tubes. They are encased in an ABS radome for total environmental protection.

Weatherproof: The ABS radome is ultraviolet inhibited. The mounting sleeve is ABS plastic with an extruded drain system to allow for any condensation dissipation.

Lightweight: These antennas are lightweight at less than 2 lbs. but are designed to easily withstand winds of over 125 MPH.

Simple Installation: Using the optional BNT mounting kit, installation takes only minutes.

Termination: This antenna is available with either an "N" female or "N" male termination. Optional reverse polarity connectors for female "N" are available as special order.



ELECTRICAL SPECIFICATIONS:

FREQUENCY:	2400-2500MHz
GAIN:	3dBi
VERTICAL BEAMWIDTH:	40°
BANDWIDTH:	100MHz@ <2:1
POWER RATING:	100 watts
IMPEDANCE:	50 ohms

MECHANICAL SPECIFICATIONS:

ANTENNA LENGTH:	8" (20cm)
WEIGHT:	2 lbs (907kg)
RADIATOR:	Copper alloy elements
RADOME:	White UV inhibited ABS
MOUNTING SLEEVE:	White UV inhibited ABS
SLEEVE DIAMETER:	1.35" (3.4cm)
TERMINATION:	BNF2403S "N" FEMALE BNM2403S "N" MALE

Vertical Pattern

