

Technical Specification
806-960 MHz 4dB Gain

BS800S, BS800SN
BASE STATION ANTENNA

Reliable Performance: Rated at 100 watts and 4dBd gain, you can expect years of continuous service. This antenna requires no ground plane.

Rugged Construction: The radiating structure is encased in a fiberglass radome to provide structural integrity.

Elegant and Functional: This antenna provides a low visibility high performance antenna at an economical price. The fiberglass radome is ultraviolet inhibited. This antenna is supplied with integrated mounting hardware for easy mounting on a 1 1/2" standard mast. This antenna is recommended for use in indoor applications. It is not recommended for applications where extreme weather conditions exist.

Lightweight: This antenna is very light weight at less than 3 lbs. and is a great performer in indoor data applications.



SPECIFICATIONS

Part No.	Frequency
BS800S-A	806-866MHz
BS800S-C	824-896MHz
BS800S-E	890-970MHz
GAIN:	4dBd
VSWR:	<2:1
BANDWIDTH:	60 MHz min.
POWER RATING:	100 watts
IMPEDANCE:	50 ohms
VERT BEAMWIDTH:	35°
RADIATOR:	Copper structure
RADOME:	White UV inhibited fiberglass
TERMINATION:	BS800S, TNC female BS800SN, N female
MOUNTING:	1-1/2" (4cm) standard mast kit supplied Optional stainless mast kit available
LENGTH:	27" (68.5cm)
WEIGHT:	<3 lbs. (1.3kg)

Vertical Pattern

