

## Technical Specification

### 806-960 MHz Unity Gain

## BSLL800UWB

### BASE STATION ANTENNA

**Reliable Performance:** Rated at 250 watts and unity gain across the 806-960MHz band, this antenna will provide years of continuous service.

**Rugged Construction:** The radiating elements are supported internally and constructed of copper alloy. They are then encased in a fiberglass radome for total environmental protection.

**Weatherproof:** The fiberglass radome is ultraviolet inhibited. The heavy wall aluminum mounting sleeve is epoxy coated for superior weather protection.

**Lightweight:** These antennas are lightweight at less than 5 lbs. but are designed to easily withstand winds of 125 MPH.

**Simple Installation:** Using the optional BSLLMNT2 or BSLLUMNT1-2 mounting kit, installation takes only minutes.



#### ELECTRICAL SPECIFICATIONS:

<b>FREQUENCY:</b>	806-960MHz
<b>GAIN:</b>	Unity
<b>VERTICAL BEAMWIDTH:</b>	70°
<b>BANDWIDTH:</b>	154MHz @ <2.0:1
<b>POWER RATING:</b>	250 watts
<b>IMPEDANCE:</b>	50 ohms

#### MECHANICAL SPECIFICATIONS:

<b>ANTENNA LENGTH:</b>	20" (50.8cm)
<b>RADIATOR:</b>	Internal copper alloy elements
<b>RADOME:</b>	2" dia. white UV fiberglass
<b>MOUNTING SLEEVE:</b>	Heavy wall epoxy coated
<b>SLEEVE LENGTH:</b>	3 ½" (8.8cm)
<b>SLEEVE DIAMETER:</b>	2.375" (3.5cm)
<b>WEIGHT:</b>	4 lbs. (1.8kg)
<b>FLAT PLATE AREA:</b>	.124 ft <sup>2</sup>
<b>WIND RATING:</b>	125 MPH (201kpg)
<b>LATERAL THRUST:</b>	8.35 lbs. (3.7kg)

**Vertical Pattern**

