

C Mount: Universal NMO type all brass mount with a piercing stainless steel saddle for the most securely grounded installation. Mounts in either a 3/8" or 3/4" hole. No problems with bending of brass mounting ears or steel corrosion.



M Mount: NMO type brass and steel mount for 3/4" hole installation.



MB Mount: NMO type all brass mount for 3/4" hole installation.



MH Mount: NMO type brass and steel mount with large center button for higher distributed capacitance and 3/4" hole installation.



MHB Mount: NMO type all brass mount with large center button for higher distributed capacitance and 3/4" hole installation.



TBML Thick Body Mount: The standard thick body mount allows for installations through body surfaces from 3/16" to 1/4" thick.



VTBML Very thick Body Mount: The very thick body mount allows for installations through body surfaces up to 1/2" thick.



UTBM Universal Thick Body Mount: This mount allows for installation through body surfaces up to 5/8" thick such as fiberglass. The UTBM mount terminates as a MINI-UHF female connector. Optional cable assemblies are available to fit most applications.



TAUHF, TAN: Thick body NMO mount adapters. TAUHF terminates in a SO239 type connector and mates with a PL259 type connector as an "N" connector.



C 3/8 or 3/4 hole mount only
CTM "C" mount with 14ft Teflon coax
CZL "C" mount with 17ft LL-195 low loss coax



M Standard 3/4 hole mount only
MTM "M" mount with 14ft Teflon coax
MZL "M" mount with 17ft LL-195 low loss coax



MB Brass insert 3/4 hole mount only
MBTM "MB" mount with 14ft Teflon coax
MBZL "MB" mount with 17ft LL-195 low loss coax



MH High distributed capacity 3/4 hole mount only
MHTM "MH" mount with 14ft Teflon coax
MHZL "MH" mount with 17ft LL-195 low loss coax



MHB High distributed capacity brass 3/4 hole mount only
MHBTM "MHB" mount with 14ft Teflon coax
MHBZL "MHB" mount with LL-195 low loss coax



TBM Mount without cable
TBMTM "TBM" mount with 14ft Teflon coax
TBMZL "TBM" mount with 17ft LL-195 low loss coax



VTBM Mount without cable
VTBMZL "VTBM" mount with 17ft LL-195 low loss coax



Choose a connector by adding suffix below

-01	TNC	(crimp on)
-02	BNC	(crimp on)
-03	PL259	(solder on)
-04	MINI UHF	(crimp on)
-05	TYPE N	(solder on)
-06	PL259	(crimp on)
-07	TYPE N	(crimp on)
-10	SMA	(crimp on)