US Office: Tel: 800.648.2800 or +1.847.671.6690 UK Office: Tel: (+44) 1543 459 555 www.mobilemark.com





IW-5900/1575

IW-5900 DSRC

These inside window mount DSRC only or combined DSRC/GPS antennas were specifically designed for ITS (Intelligent Transportation Systems), and used for Vehicle -to-Vehicle (V2V) in ITS Trials. These antennas operate on the DSRC frequency, covering 5.85-5.93 GHz.

The IW-5900/1575 is a window mounted vehicle antenna that is designed for DSRC at 5.85-5.93 GHz and GPS at 1575 MHz. The antenna uses LMR-100 cables on DSRC and RG-174 on GPS. It is housed in a single ASA plastic radome. Cable assembles of any length are available to complete the installation.

The IW-5900/1575 measures 3.56" x 3.41x .47" D (90 mm x 87mm x 12mm).

The IW-5900 DSRC antenna is designed for mounting on the inside of a vehicle windshield. The unique radome design provides internal element tilt to compensate for the tilt angle of the windshield. The cable exits near the top side allowing direct entry into the vehicle headliner.

Inside Window Mount DSRC Only & DSRC/GPS

- Both antenna styles uses 3M VHB double sided tape
- Compact and low profile designs
- Choice of DSRC-only or combined DSRC&GPS

Model #	Frequencies		
IW-5900/1575-7C2C-BLK-12	5.85-5.93 GHz (DSRC) & 1575 MHz (GPS)		
IW-5900-7C-BLK-12	5.85-5.93 GHz (DSRC)		
Optional Combination Glonass/GPS Available			
Standard connector is a SMA Plug (Male)			

Specifications			
Frequency:		Connector:	SMA Plug Standard
DSRC	5.85-5.93 GHz		Other connectors available
GPS	1575 MHz		
GLONASS (Optional)	1602 MHz	IW-5900	
VSWR:	2:1 max over range	Case:	Black ASA
Maximum Power:	10 Watts	Size:	1.63" dia. x .1.61" H
GPS Gain:	1575 +/- 2MHz, LNA 26 dB,		(4.2 mm x 4.1 mm)
	5 dBi nominal RHCP	Mounting:	Double sided 3M VHB tape
Amplifier Bias:	3.3 to 5 VDC	Cable:	LMR-100, 1ft long, (30.5cm)
Current:	20 mA max, 10 mA typical		, 0, (,
		Connector:	SMA Plug (Male)
IW-5900/1575			
Case:	Black ASA Plastic		
Size	.47" H x 3.56" W x 2.41" D	Shock & Vibration:	EN 61373, IEEE 1478,
Mounting	(12mm x 91mm x 61mm)		Mil-801-G, TIA-329.2-C
Mounting:	Double sided 3M VHB tape		
Cable:	LMR-100, 1ft (DSRC) (30cm)	Water Ingress:	IPx5
	RG-174, 1 ft long (GPS)		
	(30cm)		