



Surface Mount, Low Profile
 Wideband with GPS

Low Profile Wideband 800-2200 MHz with GPS

- Multiband antenna for GPS and Cellular Voice/Data including AWS
- Rugged case; passes industry and military shock and vibration testing

This two-cable antenna combines two applications at a time: GPS on one cable and any one of several wireless data applications on the other cable.

The LMW Series stands out from the other Mobile Mark Surface Mount Antenna Series in that it is extremely broadband and covers worldwide cellular bands from 800-960 MHz and 1700-2200 MHz, including UMTS and AWS. It has excellent performance characteristics and performs well across the entire band.

This new wideband Surface Mount Antenna offers greater flexibility for stocking and installation because it can function over multiple systems.

For GPS, the performance is 26 dB amplifier gain with 5 dBi RHCP nominal antenna gain. The antennas have low noise figure with excellent filter characteristics.

This rugged antenna can be mounted with complete confidence in a wide range of settings. It can be mounted to any vehicle, container or bulkhead with a threaded stud mount. For optimal performance, a ground plane is recommended.

Model Configurator

LMW-UMB- - -

Cable/Connector 1 └───┬───┘

Cable/Connector 2 └───┬───┘

Color └───┬───┘

Cable Length in Inches (eg. 12 or 180) └───┬───┘

Example: LMW-UMB-3C2C-WHT-180

<u>Cable Options:</u>		<u>Connector Options:</u>		<u>Color Options:</u>	
<u>Code</u>	<u>Cable</u>	<u>Code</u>	<u>Connector</u>	<u>Code</u>	<u>Color</u>
1	RG-58	A	TNC	WHT	White
2	RG-174	B	Mini UHF	BLK	Black
3	LL-195	C	SMA		

(Other Configurations available.)

Specifications	
Frequency: Cable 1 Cable 2, GPS Data Side: Gain (800 - 1250 MHz) Gain (1650 - 2200 MHz) VSWR: Nominal Impedance: Power: Operating Temp:	800 - 2200 MHz 1575.42 +/- 2 MHz 2 dBi 4 dBi 2:1 max over range 50 Ohm 20 Watts -40° to +80° C
GPS Side: Amplifier gain Antenna gain Noise Figure Amplifier Bias Amplifier Current	26 dB, LNA 5 dBi nominal RHCP, Antenna 2.0 dB max, 1.7 dB typical 2.7 to 5 VDC 20 mA max, 10 mA typical
Standard Cables: Cable 1 Cable 2 (GPS) Optional Cables: Cable 1 Connectors: Case: Case Material: Mounting:	Low Loss-195 15 ft (4.5 m) RG-174, 15 ft (4.5 m) RG-58, 15 ft (4.5 m) SMA Plug (Male) standard 3.5"D x 1.5"H (8.9 cm x 3.8 cm) UV resistant ASA 5/8" dia. x 1/2" long (1.6 cm x 1.3 cm) Up to 1/4" (6.4 mm) thick metal Nut and gasket included
Hardware: Shock & Vibration: Water Ingress:	EN 61373, IEEE 1478, MIL-810G TIA-329.2-C IPx7