

Technical Specification

A4641WN, BN

406-512 MHz

LOW PROFILE UHF TAMPERPROOF ANTENNA

Performance: These antennas provide unity gain in a design for heavy duty service. They have a power handling capacity of 200 watts.

Stylish and Durable: These antennas are manufactured using the finest materials and finishes available. The covers are molded using UV inhibited ABS plastic and are available in black or white finishes.

Reliable: The heavy duty, chrome plated brass base and gold plated spring loaded contact provide rugged and reliable performance.

Tamperproof Mounting: These antennas terminate as an "N" type connector making installation as either a ceiling mount or a bulkhead cabinet type mount.



SPECIFICATIONS:

FREQUENCY RANGE:

A4641WN-406406-420 MHzA4641WN-420420-435 MHzA4641WN-440440-450 MHzA4641WN-450450-465 MHzA4641WN-465465-480 MHzA4641WN-480480-495 MHzA4641WN-490490-512 MHz

Note: model numbers above are specifed for white (W)

GAIN: Unity
IMPEDANCE: 50 ohms
POWER RATING: 200 watts

VSWR: <2.0:1 @ 10MHz

BASE: Heavy duty, triple plated chrome

brass

 TERMINATION:
 "N" Type connector

 HEIGHT:
 2 5/8" (6.6cm)

 DIAMETER:
 1.5" (4cm)

COLOR: Specify W (White) or B (Black)

Vertical Pattern

