

A4641 Series



PRODUCT OVERVIEW

The A4641 is a Low-Profile UHF Surface Mount Antenna. It provides unity gain and is designed for heavy-duty service. It is a reliable option for Public Safety and Government agencies. It comes in a black or white finish. With rugged and reliable performance, it features a heavy-duty chrome-plated brass base and gold plated spring-loaded contact.

Two mounting options are available for this antenna. The standard configuration uses a TAD/NMO mount. The NMO mount recommended with this antenna offers an excellent moisture seal, even when the antenna is removed. Alternatively, the antenna can be configured with an "N" type connector exiting the base of the antenna. This antenna style is recommended for tamperproof installations. It can also be used as a ceiling mount or a bulkhead cabinet type mount.

Comtelco is Now a Mobile Mark Brand.

Visit our eStore to customize an Antenna Online.

Electrical Specifications					
A4641 <mark>B</mark> -406	406 - 420 MHz				
A4641B-420	420 - 435 MHz				
A4641B-440	440 - 450 MHz				
A4641B-450	450 - 465 MHz				
A4641B-465	465 - 480 MHz				
A4641B-480	480 - 490 MHz				
A4641B-490	490 - 512 MHz				
	A4641B-406 A4641B-420 A4641B-440 A4641B-450 A4641B-465 A4641B-480				

"B" in above SKUs represent the Black Finish Models. Replace with "W" for a White Finish, and add "N" for the Female "N" Termination Option. See Colored Nomenclature example on the top right.

VSWR < 2.0:1 Power Rating 200 Watts	Gain	Unity
	VSWR	< 2.0:1
	Power Rating	200 Watts
Impedance 50 Ohms	Impedance	50 Ohms

Mechanical Specifications

Radome Material/Finish	UV inhibited ABS plastic Available in Black or White finishes.			
Dimension	A4641B, W	2 3/4" (6.9cm) Height 1.5" (4cm) Diameter		
Dimensions	A4641BN, WN	2 5/8" (6.6cm) Height 1.5" (4cm) Diameter		
Connector or Mount	A4641B, W	Standard TAD/NMO Type with Spring Loaded Contac		
	A4641BN, WN	"N" Female Type Connector & Triple Plated Chrome Base		

Vertical Pattern





LOW PROFILE UHF ANTENNA

Α	4	6	4	1	W	Ņ	-	4	5	0
Mo	ode									
Со	lor:	"W'	″ or	"B"						
"N	″ Fe	mal	le O	ptic	on –					
Fre	eau	encv	/ Re	fere	ence					

HIGHLIGHTS:

- Compact & Low-Profile
- Tamperproof Option Available
- Convenient Alternative Whip Style
- Heavy Duty Construction
- Made-in-the-USA & UK

RELATED MODELS:

- A55136TBS
- (Tri-Band Whip)
- A46450BNT
- (Wideband UHF Stud Mount) • LLPG304
 - (Multiband UHF Surface Mount)

COMMON APPLICATIONS:

- Public Safety
- Government Agencies
- Fire, Police & Ambulances



US Headquarters +1.847.671.6690 US/CA Toll Free +1.800.648.2800 European Facility +44.1543.459555

www.MobileMark.com