

Technical Specification

A11331 A, B

VHF/UHF/800MHz

TRI BAND MOBILE ANTENNA

Performance: These antennas provide unity gain on VHF and UHF and 800MHz in three frequency ranges.

Stylish and Durable: This antenna is manufactured using the finest corrosion resistant materials and finishes available. It is available in triple plated chrome or black finish.

Reliable: The ABS base has an ultrasonically welded brass insert and a gold plated spring loaded contact. The silver plated matching coil is fully enclosed to insure years of dependable service.

Standard Mounting: These antennas are designed to mate with a standard TAD/NMO type mount.

ELECTRICAL SPECIFICATIONS:

FREQUENCY RANGE: X Y Z

144-160MHz 150-165MHz 150-174MHz 435-460MHz 450-470MHz 450-475MHz 885-970MHz 806-940MHz 825-895MHz

GAIN: Unity
VSWR: <2:1
IMPEDANCE: 50 ohms
POWER RATING: 200 watts

MECHANICAL SPECIFICATIONS:

RADIATOR: Stainless steel

MATCHING COIL:Silver plated, enclosed coilBASE:ABS, Ultrasonic brass insertCONTACT:Gold plated spring loaded contact

LENGTH: 19" (48cm)
FINISH: Brite or Black

MOUNTING: Standard TAD/NMO type

