

**Technical Specification**

**B46DB630WN,BN**

**698-960 1850-2200 MHz LOW PRO DUAL BAND TAMPERPROOF ANTENNA**

**Performance:** These antennas provide at least unity gain (frequency dependant) in a design for heavy duty service. They have a power handling capacity of 200 watts.

**Stylish and Durable:** These antennas are manufactured using the finest materials and finishes available. The covers are molded using UV inhibited ABS plastic and are available in black finish.

**Reliable:** The heavy duty, brass base and "N" termination provide rugged and reliable performance. A ground plane is required for proper operation.

**Tamperproof Mounting:** These antennas terminate as an "N" Type connector making installation simple.

These parts are supplied with a 13" ground plane.



**SPECIFICATIONS:**

**FREQUENCY RANGE:** 698-960 1850-2200MHz  
**GAIN:** >Unity  
**IMPEDANCE:** 50 ohms  
**POWER RATING:** 200 watts  
**VSWR:** 698-960 1850-2200 <2.0:1  
 698-960 1850-3000 2.5:1  
**TERMINATION:** "N" Type connector  
**HEIGHT:** 4 1/8" (10cm)  
**DIAMETER:** 1.5" (4cm)  
**COLOR:** -B Black or -W White  
 B46DB630BN,WN

**Vertical Pattern**

