

## Technical Specification 746-796MHz 5dBd, 7dBi Gain

## BS750XL5 BASE STATION ANTENNA

**Reliable Performance:** Rated at 250 watts, you can expect years of continuous service.

**Rugged Construction:** The radiating elements are supported internally and constructed of copper alloy. They are then encased in a fiberglass radome for total environmental protection.

**Weatherproof:** The fiberglass radome is ultraviolet inhibited. The heavy wall aluminum mounting sleeve is epoxy coated for superior weather protection.

**Lightweight:** These antennas are lightweight at less than 8 lbs. but are designed to easily withstand winds of over 125 MPH.

**Simple Installation:** Using the optional BSMNT2 mounting kit, installation takes only minutes.

### ELECTRICAL SPECIFICATIONS:

<b>FREQUENCY:</b>	746-796MHz
<b>GAIN:</b>	5dBd
<b>VERTICAL BEAMWIDTH:</b>	30°
<b>BANDWIDTH:</b>	50MHz@ <2.0:1
<b>POWER RATING:</b>	250 watts
<b>IMPEDANCE:</b>	50 ohms

### MECHANICAL SPECIFICATIONS:

<b>ANTENNA LENGTH:</b>	62" (1.5m)
<b>WEIGHT:</b>	< 8 lbs (4kg)
<b>RADIATOR:</b>	Internal copper alloy elements
<b>RADOME:</b>	White UV inhibited fiberglass
<b>MOUNTING SLEEVE:</b>	Heavy wall epoxy coated
<b>SLEEVE DIMENSIONS:</b>	1.35" (3.4cm) x 10" (25.4cm)
<b>FLAT PLATE AREA:</b>	.24 ft <sup>2</sup>
<b>WIND SURVIVAL:</b>	125 MPH (201kph)
<b>LATERAL THRUST:</b>	16.1 lbs. (7.3kg)



**Vertical Pattern**

