

## **Technical Specification**

## **BS5408NM**

# 5.47-5.725GHz, 6dBd / 8dBi Gain

### **BASE STATION ANTENNA**

Reliable Performance: Rated at 50 watts, you can expect years of continuous service.

**Construction:** The radiating elements are encased in an ABS radome for total environmental protection.

**Lightweight:** These antennas are lightweight at less than 1 lb. and are designed to easily withstand winds of over 125 MPH.

**Simple Installation:** This antenna does not require any special mounting hardware.

**Termination:** This antenna terminates as a Male "N" connector.



#### **ELECTRICAL SPECIFICATIONS:**

 FREQUENCY:
 5.47-5.725GHz

 GAIN:
 6dBd / 8dBi

**VERTICAL BEAMWIDTH:** 35°

**BANDWIDTH:** ~200MHz@ <2:1

POWER RATING: 50 watts IMPEDANCE: 50 ohms

#### **MECHANICAL SPECIFICATIONS:**

ANTENNA LENGTH: 8" (20cm)
WEIGHT: <1 lb. (2.54cm)
RADIATOR: Brass elements

**RADOME:** White UV inhibited ABS

(Available in Black add B suffix)

**SLEEVE DIAMETER:** 1/2" (1.27cm)

FLAT PLATE AREA: .03 ft<sup>2</sup>

WIND RATING: 125 MPH (201kph)
WIND LOAD: 2.2 lbs. (997g)
TERMINATION: "N" Male

#### Vertical Pattern

