

Technical Specification

75-140 MHz Unity Gain

BSL100U

BASE STATION ANTENNAS

Reliable Performance: Rated at 250 watts and unity gain, you can expect years of continuous service from this heavy duty antenna.

Rugged Construction: The radiating elements are supported internally and constructed of copper alloy. They are welded and/or soldered to prevent any intermodulation. They are then encased in a fiberglass radome for total environmental protection.

Weatherproof: The fiberglass radome is ultraviolet inhibited. The heavy wall aluminum mounting sleeve is epoxy coated for superior weather protection.

Lightweight: These antennas are lightweight at less than 10 lbs. but are designed to easily withstand winds of over 125 MPH.

Simple Installation: Using the optional BSLMNT2 or our new heavy duty BSLLUMNT2-4 mounting kit, installation takes only minutes.

ELECTRICAL SPECIFICATIONS:

FREQUENCY RANGE: 75MHz – 140MHz
VSWR: <2.0:1
BANDWIDTH: 6MHz @ <2:1
POWER RATING: 250 watts
IMPEDANCE: 50 ohms
VERTICAL BEAMWIDTH: 75°

MECHANICAL SPECIFICATIONS:

RADIATOR: Internal copper alloy elements
RADOME: 1.5" (4cm) dia. white UV inhibited fiberglass
MOUNTING SLEEVE: 10" (25.4cm) heavy wall epoxy coated
SLEEVE DIAMETER: 1.95" (4.9cm)
TERMINATION: Female N
ANTENNA LENGTH: 96" (2.43m) at lowest frequency
WEIGHT: 10 lbs. (4.5kg)
FLAT PLATE AREA: .66 ft²
WIND RATING: 125 MPH (201kph)
LATERAL THRUST: 44.5 lbs. (20.1kg)



Vertical Pattern

