

Technical Specification

1710-1850MHz, 8dBi Gain

BSL1710XL6

BASE STATION ANTENNA

Reliable Performance: Rated at 250 watts, you can expect years of continuous service.

Rugged Construction: The radiating elements are supported internally and constructed of copper alloy. They are then encased in a fiberglass radome for total environmental protection.

Elegant and Weatherproof: The fiberglass radome is ultraviolet inhibited. The heavy wall aluminum mounting sleeve is epoxy powder coated for superior weather protection.

Lightweight: These antennas are lightweight at less than 4 lbs.

Simple Installation: These antennas are terminated with an N type female connector or an optional pigtail.

ELECTRICAL SPECIFICATIONS:

FREQUENCY:	1710-1850MHz
GAIN:	8dBi (6dBd)
VERT BEAMWIDTH:	20°
BANDWIDTH:	140MHz@ <2.0:1
POWER RATING:	250 watts
IMPEDANCE:	50 ohms

MECHANICAL SPECIFICATIONS:

RADIATOR:	Internal copper alloy elements
RADOME:	1.5" (4cm)dia. white UV fiberglass
OVERALL LENGTH:	24" (61cm)
TERMINATION:	Female "N"
MOUNTING SLEEVE:	1.95" dia (4.9cm)
WEIGHT:	3.2 lbs (1.4kg)
FLAT PLATE AREA:	.125 ft ²
WIND RATING:	125 MPH (201kph)
LATERAL THRUST:	7.6 lbs (3.4kg)



Vertical Pattern

