

Technical Specification

1.85-1.99GHz, 8dBi Gain

BSL1850XL6

BASE STATION ANTENNA

Reliable Performance: Rated at 250 watts, you can expect years of continuous service.

Rugged Construction: The radiating elements are supported internally and constructed of copper alloy. They are then encased in a fiberglass radome for total environmental protection.

Elegant and Weatherproof: The fiberglass radome is ultraviolet inhibited. The heavy wall aluminum mounting sleeve is epoxy powder coated for superior weather protection.

Lightweight: These antennas are lightweight at less than 5 lbs.

Simple Installation: These antennas are terminated with an N type female connector or an optional pigtail.



ELECTRICAL SPECIFICATIONS:

FREQUENCY:	1850-1990MHz
GAIN:	8dBi (6dBd)
VERT BEAMWIDTH:	20°
BANDWIDTH:	140MHz@ <2.0:1
POWER RATING:	250 watts
IMPEDANCE:	50 ohms

MECHANICAL SPECIFICATIONS:

RADIATOR:	Internal copper alloy elements
RADOME:	1.5" (4cm)dia. white UV fiberglass
OVERALL LENGTH:	24" (61.cm)
TERMINATION:	Female "N"
MOUNTING SLEEVE:	1.95" (4.9cm)dia. X 3 1/2" (8.8cm)long
WEIGHT:	4 lbs (1.8kg)
FLAT PLATE AREA:	.125 ft ²
WIND RATING:	125 MPH (201kph)
LATERAL THRUST:	6 lbs.(2.7kg)

Vertical Pattern

