

Technical Specification

144-174MHz, 220-225MHz Unity Gain

BASE STATION ANTENNA

Reliable Performance: Rated at 250 watts and unity gain, you can expect years of continuous service from this heavy duty antenna.

Rugged Construction: The radiating elements are supported internally and constructed of copper alloy. They are welded and/or soldered to prevent any intermodulation. They are then encased in a fiberglass radome for total environmental protection.

Weatherproof: The fiberglass radome is ultraviolet inhibited. The heavy wall aluminum mounting sleeve is epoxy coated for superior weather protection. Full moisture drain system.

Lightweight: These antennas are lightweight at less than 10 lbs. but are designed to easily withstand winds of 125 MPH.

Simple Installation: Using the optional BSLLMNT2 or BSLLUMNT2-4 mounting kit, installation takes only minutes.

ELECTRICAL SPECIFICATIONS:

ANTENNA TYPE:	FREQUENCY:
BSLL150U-A	144-148MHz
BSLL150U-B	150-156MHz
BSLL150U-C	156-162MHz
BSLL150U-D	162-168MHz
BSLL150U-E	168-174MHz
BSLL220U-A	220-210MHz
BSLL220U-B	210-220MHz
BSLL220U-C	215-225MHz
BANDWIDTH:	6MHz <2.0:1 VSWR
VERTICAL BEAMWIDTH:	75°
POWER RATING:	250 watts
IMPEDANCE:	50 ohms

MECHANICAL SPECIFICATIONS:

RADIATOR:	Internal copper alloy elements
RADOME:	2" (5cm)dia. UV inhibited fiberglass
MOUNTING SLEEVE:	10" 25.4cm)heavy wall epoxy coated
SLEEVE DIAMETER:	2.375" 96cm)
ANTENNA LENGTH:	64" (1.62cm) Maximum
WEIGHT:	10 lbs. (4.5kg)
FLAT PLATE AREA:	.44 ft ²
WIND RATING:	125 MPH (201kph)
LATERAL THRUST:	29.7 lbs. (13.4kg)



Vertical Pattern

