

## **Technical Specification**

## **SPECIALTY MOUNTS**

**TMBM, TMBC** Trunk Mounting Bracket: Stainless steel bracket with stainless screws. 3/4" or 3/8" hole and black or brite finish available. 3/8" version accepts C mount. Designed for permanent installation on trunk lid.



MMM Commercial Mirror Bracket: Mirror bracket with 3/8" hole to accept C mount. Black powder coat finish.



**MMNMO** Complete Mirror Mount: Mirror bracket with NMO mount and 17 feet of RG58 coax. Black powder coat finish.



**BSMN Mirror Mount NMO:** Mirror bracket with NMO mount terminated with an "N" type connector. Black powder coat finish.



**UNIBKT:** Universal mounting bracket with .625" dia. hole. (accepts "N" type connector) Black powder coat finish.



**UTBM Universal Thick Body Mount:** This mount allows for installation through body surfaces up to 5/8" thick such as fiberglass. The UTBM mount terminates as a MINI-UHF female connector. Optional cable assemblies are available to fit most applications.



**UTCM Universal Ceiling Mount:** Allows for easy installation of NMO based products through standard ceiling tile. Comes complete with white ground plane plate for UHF, 800MHz, 1.8GHz, 2.4GHz and 5GHz ceiling mounted products.



**TAUHF, TAN:** Thick body NMO mount adapters. TAUHF terminates in a SO239 type connector and mates with a PL259 type male. TAN terminates as an "N" connector.

