

Technical Specification

Y441810

YAGI ANTENNA

1710/1880 MHz YAGI

High Performance: This 10 element yagi antenna provides 10dBd gain with wide band performance.

Rugged and weatherproof: Our radome enclosed construction provides excellent weather protection for our solid element U channel yagi antennas. The radome is constructed of UV inhibited ABS. The heavy duty mounting plate is extruded aluminum. Stainless steel V bolts are provided for long term reliability and resistance to corrosion.

Lightweight and Durable: This yagi antenna is easily installed by one person, yet is designed to withstand 125 MPH winds.

Termination Options:

Type A: 12" (30cm) Teflon pigtail with N connector.

MECHANICAL SPECIFICATIONS

MATERIAL: 1/2" (1.27cm) aluminum U channel boom

3/16" solid elements

RADOME: 3" (7.6cm)UV inhibited ABS

LENGTH: 19" (48cm) **WEIGHT:** 2 lb. (907g)

MOUNTING: 2 1/2" (6.35cm)mast maximum WIND SURVIVAL 125 MPH + (201kph)



ELECTRICAL SPECIFICATIONS

GAIN: 10.dBd

FREQUENCY: 1710-1880MHz

F to B RATIO: 20dB
BANDWIDTH: 170MHz
VSWR: <2:1

POWER RATING: 150 watts IMPEDANCE: 50 ohms