



IMAG5 Series



MGD Series 2.4 & 4.9-6 GHz

## Magnet Mount Antennas WiFi, 2.4 & 2.4/4.9-6 GHz

- Single band for 2.4 GHz, dual band models for 2.4-2.5 & 4.9 - 6 GHz
- Built-in ground plane improves high frequency performance
- Low profile, powerful magnet securely holds antenna

Mobile Mark's high frequency Magnet Mount antennas are useful for many applications including surveillance work, 2.4 WiFi/ISM, and other high frequency applications. Their unique design features allow them to overcome many of the problems normally associated with higher frequency systems.

The IMAG Series mag-mounts have a ground plane at the feedpoint. This design overcomes the typical ground decoupling that occurs at the higher frequencies.

Because the IMAG antennas have their own built-in ground plane but will require a metal surface to be mounted. Available in either a unity gain (0 dBi) or 5 dBi.

The IMAG Series are very small in design and appearance. A powerful mini magnet holds the antenna securely at all times. The 3" round (76 mm) integral ground plane on the IMAG5 can serve as a removal handle.

The low profile 5 dBi whip with tight winding phasing coil reduces potential whistling noise.

The MGD-2400/5500 antenna operates on WiFi 2.4 & 5 GHz and can also be used for public safety 4.9 GHz and DSRC 5.9. It is typically supplied with an SMA plug connector, others are available.

A steel surface (but not stainless steel) will provide best contact with the powerful magnet. All units are supplied with a choice of RF connectors.

Standard cable supplied is low loss-195, which has excellent electrical characteristics.

Model #	Gain	Frequency
MGD-2400/5500-3C-BLK-120	2.5 dBi	2.4-2.5 & 4.9-6 GHz
MGD-2400/5500-3C-WHT-120	2.5 dBi	2.4-2.5 & 4.9-6 GHz
IMAG5-2400-3C-BLK-120	5 dBi	2400-2485 MHz
Available in WHT-White or BLK-Black		

Specifications			
Frequency:	See above	MGD Radome:	White or black ASA plastic
Gain:	See above	IMAG Whip:	302 stainless steel
VSWR:	2:1 over band	Cable:	10 feet (3 meters) of LL-195
Impedance:	50 Ohm nominal	Connector:	SMA Plug (Male) standard
Maximum Power:	10 Watts	Shock & Vibration:	MGD series, EN 61373, IEEE 1478, MIL-810G TIA-329.2-C
Operating Temp:	-40° to +85° C		
Antenna Height: IMAG5 series	4 7/8 inches (124 mm)		
MGD Size:	1.9" High x 3.4" Diameter (48 mm x 86 mm)		
IMAG Mount:	ASA plastic & metal		